

FEATURES

- Optimal Unloading Tube Position: The unloading tube is uniquely angled for superior grain discharge, enhancing both speed and efficiency. This feature boosts discharge performance while minimising fuel consumption
- Improved Discharge Visibility: With excellent visibility of the discharge spout, operators can easily monitor and precisely guide grain into the hopper, ensuring seamless and efficient transfer
- Sliding Bottom Doors and Side Access Hatches: Designed to streamline the unloading process while allowing easy cleaning access, reducing downtime and maintenance efforts.
- Additional Features: Easy wind tarp, tool box for convenient storage, integrated clearance lights, anti-slip folding ladder, rear tow hitch and front panels with wide windows
- Electric scales and pivoting spout (Optional)

			_	
TECL		SPECIF	'IC ATI	ONIC
1 - (-	IIVII AI	SPELIE	α	
		JI LCII	I CALL	

Maximum loading capacity (kg)	25,000	
Capacity (L)	32,000	
Discharge performance (kg/min)	12,000	
Unloading tube diameter (min)	507	
Power required (HP)	160	
Gearbox (rpm)	540 / (1000 optional)	
Overall Width (mm)	3,341	
Bin Height	3,781	
Ground to Spout Height	4,386	
Bin Length	5,990	
Chassis length	5,050	
Tyre width (mm) may vary acc to tyre	3,491	





